

(中国产)		型号	MMU-UP	0091HY-C	0121HY-C	0151HY-C	0181HY-C	0241HY-C	0271HY-C	0301HY-C	0341HY-C	0361HY-C	0421HY-C	0481HY-C	0561HY-C				
制冷量			(kW)	2.8	3.6	4.5	5.6	7.1	8.0	9.0	10.0	11.2	12.5	14.0	16.0				
制热量			(kW)	3.2	4.0	5.0	6.3	8.0	9.0	10.0	11.2	12.5	14.0	16.0	18.0				
使用电源		单相220V 50Hz																	
运行电流			(A)	0.23		0.27	0.29	0.38		0.43	0.50	0.73		0.88					
耗电量			(kW)	0.021		0.023	0.026	0.036		0.043	0.055	0.088		0.112					
启动电流			(A)	0.30		0.33	0.36	0.42		0.59	0.67	0.87		1.23	1.26				
外形尺寸		高/宽/深		(mm)		256/840/840						319/840/840							
重量			(kg)	19		21						25							
面板	面板型号		RBC-U32PGP(W)-C 颜色:月白色																
	面板尺寸		高/宽/深		(mm)		30/950/950												
	面板重量		(kg)		4.0														
标准风量			(m ³ /h)	800/730/680		930/ 830/790	1050/ 920/800	1290/920/800		1320/ 1100/850	1420/ 1180/900	1970/1430/1070		2130/ 1430/1130	2130/ 1520/1230				
空气过滤网		标准长效滤网																	
控制器		选配																	
连接管道	气管		(mm)		φ9.5		φ12.7		φ15.9										
	液管		(mm)		φ6.4						φ9.5								
	排水口		(mm)		25														
运转音			dB(A)	30/29/27		31/29/27	32/29/27	35/31/28		38/33/30	43/38/32		46/38/33	46/40/33					

注：制冷：室内空气温度27℃干球/19℃湿球，室外空气温度35℃干球。制热：室内空气温度20℃干球，室外空气温度7℃干球/6℃湿球。

所示运转音为消音室内检测值，实际安装时的检测值因受周围噪音及反射回音等影响，一般高于此处所示值。