

(日本产) 型号 MMD-UP		0071 M(P)H-C	0081 M(P)H-C	0091 M(P)H-C	0101 M(P)H-C	0121 M(P)H-C	0141 M(P)H-C	0151 M(P)H-C	0171 M(P)H-C	0181 M(P)H-C	0201 M(P)H-C	0241 M(P)H-C	0271 M(P)H-C		
制冷量	(kW)	2.2	2.5	2.8	3.2	3.6	4.0	4.5	5.0	5.6	6.3	7.1	8.0		
制热量	(kW)	2.5	2.8	3.2	3.6	4.0	4.5	5.0	5.6	6.3	7.1	8.0	9.0		
电源		单相220V 50Hz													
启动电流	不带泵/带泵 (A)	0.29/0.31		0.31/0.33	0.33/0.34		0.37/0.38	0.35/0.37	0.39/0.41		0.58/0.59		0.62/0.64		
耗电量	不带泵/带泵 (kW)	0.032/0.036		0.034/0.038	0.036/0.040		0.040/0.044	0.036/0.040	0.042/0.046		0.066/0.070		0.071/0.075		
运行电流	不带泵/带泵 (A)	0.51/0.54		0.54/0.58	0.58/0.60		0.65/0.67	0.61/0.65	0.68/0.72		1.02/1.03		1.09/1.12		
外形尺寸	高/宽/深 (mm)	210/700/450						210/900/450			210/1100/450				
重量	(Kg)	16						19			22				
标准风量	(m <sup>3</sup> /h)	540/510/470/420/400		570/540/ 500/450/430	600/570/520/480/440		630/590/ 550/500/470	690/660/ 640/600/550	780/770/760/670/660			1080/1030/950/910/860		1140/1060/ 980/940/910	
机外静压	(Pa)	10(出厂设定)-20*										10(出厂设定)-20-30*			
控制器		选配													
连接 管道	气管 (mm)	φ9.5						φ12.7			φ15.9				
	液管 (mm)	φ6.4										φ9.5			
	排水口 (mm)	25													
运转音	dB(A)	31/30/29/27/26			32/31/29/28/27			33/32/ 31/29/28	34/33/ 32/30/29	35/34/33/31/30			36/35/33/32/31		37/35/ 34/33/32
3D立体 导风板 (选配)	型号	TCB-TDL0141SDY-C						TCB-TDL0181SDY-C			TCB-TDL0271SDY-C				
	尺寸高/宽/深 (mm)	180/810/70(面板厚度10)						180/1010/70(面板厚度10)			180/1210/70(面板厚度10)				

注：制冷：室内空气温度27℃干球/19℃湿球，室外空气温度35℃干球。制热：室内空气温度20℃干球，室外空气温度7℃干球/6℃湿球。(P)代表配备水泵。

所示运转音为消音室内检测值，实际安装时的检测值因受周围噪音及反射回音等影响，一般高于此处所示值。

\*如需设定45Pa机外静压，请咨询东芝空调厂方技术人员现场设定。